



# kaza

## 600x600MM / 600x1200MM

| TEST DESCRIPTION                        | TEST METHOD        | ISO STANDARD 13006 B1A TILES          | VALUE                                 |
|-----------------------------------------|--------------------|---------------------------------------|---------------------------------------|
| Length And Width                        | BS EN ISO 10545-2  | ± 0.6%                                | ± 0.3%                                |
| Thickness                               | BS EN ISO 10545-2  | ± 5.0%                                | ± 3.0%                                |
| Straightness Of Sides                   | BS EN ISO 10545-2  | ± 0.5%                                | ± 0.3%                                |
| Rectangularity                          | BS EN ISO 10545-2  | ± 0.6%                                | ± 0.3%                                |
| Surface Flatness                        | BS EN ISO 10545-2  | ± 0.5%                                | ± 0.3%                                |
| Water Absorption                        | BS EN ISO 10545-3  | ≤ 0.5%                                | ≤ 0.05%                               |
| Breaking Strength                       | BS EN ISO 10545-4  | ≤ 1300N                               | ≤ 1500N                               |
| Modulus Of Repture                      | BS EN ISO 10545-4  | ≤ 35N/MM <sup>2</sup>                 | ≤ 45N/MM <sup>2</sup>                 |
| Resistance To Deep Abrasion             | BS EN ISO 10545-6  | ≤ 175MM <sup>3</sup>                  | ≤ 150MM <sup>3</sup>                  |
| Linear Thermal Expansion                | BS EN ISO 10545-8  | ≤ 9x10 <sup>-6</sup> °C <sup>-1</sup> | ≤ 7x10 <sup>-6</sup> °C <sup>-1</sup> |
| Thermal Shock Resistance                | BS EN ISO 10545-9  | No Visible Defect                     | No Visible Defect                     |
| Frost Resistance                        | BS EN ISO 10545-12 | Frost Proof                           | Frost Proof                           |
| Resistance To Chemicals                 | BS EN ISO 10545-13 | No Visible Effect                     | No Visible Effect                     |
| Resistance To Stains                    | BS EN ISO 10545-14 | Manufacturer To State Class           | Stains Removed Min Class <sup>2</sup> |
| Colour Resistance                       | BS EN ISO 10545-16 | No Damage                             | No Damage                             |
| Colour Resistance To UV Light           | DIN 51094          | No Change In Color                    | No Change In Color                    |
| Scratch Hardness (MOH's Scale)          | EN 101             | ≥ 6 MOH'S                             | ≥ 7 MOH'S                             |
| Surface Quality                         | BS EN 10545-2      | Min. 95%                              | No Visible Effect                     |
| Skid Resistance (friction Co-efficient) | BS EN 10545-17     | >0.4                                  | >0.4                                  |
| Moisture Expansion                      | -                  | Nill                                  | Nill                                  |

### PACKING DETAILS

| DIMENSION  | PIECES | WEIGHT PER BOX | COVERAGE      |
|------------|--------|----------------|---------------|
| 600x1200MM | 2      | 28 KG          | 1.44 Sq. MTR. |
| 600x600MM  | 4      | 26.5 KG        | 1.44 Sq. MTR. |

DISCLAIMER : We tiles reserve the right to deleted and amend either totally or partially, any of the colors, shape, sizes, references and other technical specification contained in this catalogue at anytime. The colors shown of tiles in this catalogue are purely illustrative and limited to printing process. Please refer actual sample before final selection. The details of sizes, colors, references should be verified for typographical errors.

